

# ITA 41

## PNEUMATIC STEEL STRAPPING TOOL WITH SEAL JOINT



TECHNICAL SPECIFICATIONS	
<b>DIMENSIONS</b>	
Length	430mm • 16.9"
Width	260mm • 10.2"
Height	310mm • 12.2"
Weight	10.3 kgs • 22.6lbs
<b>FEEDING</b>	
Pressure range	5.5-7 bar / 78 -99 psi
Air consumption	12 L/s – 25 cuft/min
<b>PERFORMANCE</b>	
Max. tension force	9000N -6.5bar-92psi
Tensioning speed	6mt/m
Sealing	Seal double notches
Joint strength	80% of breaking strength*
Gear ratio	-

\* variable according to strap type

MODEL			
CODE	TYPE	STRAP	THICKNESS
T411943	ITA41 - 3/4" - 9000N-3B	R 850N/mm <sup>2</sup>	0.024" - 0.039"
		R 1100N/mm <sup>2</sup>	0.025" - 0.031"
T412543	ITA41 - 1" - 9000N-3B	R 850N/mm <sup>2</sup>	0.024" - 0.039"
		R 1100N/mm <sup>2</sup>	0.025" - 0.031"
T413243	ITA41 - 1 1/4" - 9000N-3B	R 850N/mm <sup>2</sup>	0.024" - 0.039"
		R 1100N/mm <sup>2</sup>	0.025" - 0.031"

 **BESTRAP**<sup>®</sup>  
La reggetta

**Praim** S.r.l  
[www.praimsrl.com](http://www.praimsrl.com)

Via Don Giovanni Minzoni  
23844 Sirone (LC)

**T:** +39 031 875019  
**F:** +39 031 851704

**@:** [info@praimsrl.com](mailto:info@praimsrl.com)  
**PEC:** [praimsrl@enetpec.it](mailto:praimsrl@enetpec.it)

a company of



**GALBIATI FAMILY**