

ITA 52

PNEUMATIC STEEL STRAPPING TOOL WITH SEAL JOINT



TECHNICAL SPECIFICATIONS	
DIMENSIONS	
Length	430mm • 16.9"
Width	260mm • 10.2"
Height	310mm • 12.2"
Weight	11.3 kgs • 22.6lbs
FEEDING	
Pressure range	5.5 -7 bar / 78 -99 psi
Air consumption	12 L/s – 25 cuft/min
PERFORMANCE	
Max. tension force	9000 N 6 bar - 87 psi
Tensioning speed	6mt/m
Sealing	Seal double notches
Joint strength	80% of breaking strength*
Gear ratio	-

* variable according to strap type

MODEL			
CODE	TYPE	STRAP	THICKNESS
T521943	ITA52-19mm-9000N- 2B	R 850N/mm ²	0.6mm 0.024" – 1mm 0.039"
		R 1100N/mm ²	0.63mm 0.025" – 0.8mm 0.031"
T522543	ITA52-25mm-9000N- 2B	R 850N/mm ²	0.6mm 0.024" – 1mm 0.039"
		R 1100N/mm ²	0.63mm 0.025" – 0.8mm 0.031"
T523243	ITA52-32mm-9000N- 2B	R 850N/mm ²	0.6mm 0.024" – 1mm 0.039"
		R 1100N/mm ²	0.63mm 0.025" – 0.8mm 0.031"

 **BESTRAP**
La reggetta

Praim S.r.l
www.praimsrl.com

Via Don Giovanni Minzoni
23844 Sirone (LC)

T: +39 031 875019
F: +39 031 851704

@: info@praimsrl.com
PEC: praimsrl@enetpec.it

a company of



GALBIATI FAMILY